



KEEP MOVING

WITH WASP BAGGAGE CARTS

Don't let a lightweight cart stop you in your tracks. Our baggage carts easily carry as much as 8,000 pounds so you won't need to worry about overloading it or using additional carts to get the job done. Not only are they stronger, they're more robust. We use thicker material, strong welds and more ribs and welding on the inside panels to make sure they hold up to anything you toss at them. Plus, the bolted-on running gear makes maintenance a breeze.

Our engineers will work closely with your safety team to custom design carts that achieve any expectation. That partnership only enhances what are already the safest products in the industry.

Thought and engineering expertise go into every component to ensure your carts keep you moving — always.



- An engineer-designed towbar and hitch allow for safe movement at 20-25 mph (32-40 kph) while preventing damage caused by jackknifes.
- All of our welders are certified by the American Welding Society, so they know how to produce strong, precision welds that last.
- Full 360-degree fifth wheel rotation allows the carts to track correctly in any direction for safety and easy maneuverability.
- Bolt-in shelves, flat or V-style floors and one or both side openings can be customized to your specifications in either 5-by-10-foot (152-by-305-centimeter) or 5-by-12-foot (152-by-366-centimeter) sizes.
- The four-wheel independent rubber torsion axles can be individually replaced on the torsion axle baggage/cargo cart model for reduced maintenance expense and downtime.
- Knock down each cart to half of its size and stack as many as three to five high for shipping. Quickly reassemble with just hand tools while following the illustrated instructions to save time and expense.
- We use thicker-gauge steel, more strengthening ribs, strong welds, premium hardware, and a shot-blast/powder-coat process to ensure our carts last and work efficiently for years.
- Designed to suit any customer requirement, whether center shelf, back wall or curtain assemblies are needed.
- U.S. military-grade custom-color powder coating keeps the cart looking new and optional hot-dip galvanizing further resists corrosion.
- Rigid mounted or torsion axle running gear styles offer choices to suit each environment.

RIGID-MOUNT CART	TORSION AXLE CART
NIGID-WOOMI CANI	I UNSIUM AALE GANI

WIDTH	65 inches (165 cm)		
LENGTH	120 or 144 inches (305 or 366 cm)		
HEIGHT	80 inches (203 cm)		
CAPACITY	8,000 pounds (3,629 kg)		
WEIGHT	1,500 pounds (680 kg)	1,750 pounds (794 kg)	
TRACK WIDTH	52-3/4 inches (134 cm)		
TIRES	Solid 4 x 8-inch, 16-inch diameter with 9 GA, 5-bolt, 4-1/2-inch BC, 2-piece demountable rims		
KING PIN	2-inch diameter stress-proof with sealed Timken bearings		
REAR HITCH	Spring-loaded E-hitch; additional options available		
CORNER BUMPERS	Smooth vinyl or optional Magee Finned		
CURTAINS	Vinyl with webbed reinforcement		
RUNNING GEAR	Rigid mount	4-wheel independent rubber torsion axles	

RIGID-MOUNT CART

TORSION AXLE CART

WIDTH	67 inches (170 cm)	
LENGTH	120 or 144 inches (305 or 366 cm)	
HEIGHT	80-1/4 inches (204 cm)	
CAPACITY	8,000 pounds (3,629 kg)	
WEIGHT	1,636 pounds (742 kg)	
TRACK WIDTH	52-3/4 inches (134 cm)	
TIRES	Solid 4 x 8-inch, 16-inch diameter with 9 GA, 5-bolt, 4-1/2-inch BC, 2-piece demountable rims	
KING PIN	2-inch diameter stress-proof with sealed Timken bearings	
REAR HITCH	Spring-loaded E-hitch; additional options available	
CORNER BUMPERS	Smooth vinyl or optional Magee Finned	
CURTAINS	Vinyl with webbed reinforcement	
RUNNING GEAR	Rigid mount	4-wheel independent rubber torsion axles

OPEN CARTS

COMBINE HIGH CAPACITY WITH EASY LOADING

Take on 8,000 pounds (3,629 kilograms) of baggage and move it at 20-25 mph (32-40 kph) with our rugged, heavy-duty open carts.



- Fifth-wheel steering with full 360-degree rotation to maximize maneuverability.
- Every piece of equipment we manufacture has to pass the test, literally. We conduct the most rigorous product testing in the industry, using strain gauges, washboard tracks and other intensive measures.
- Anti-friction Timken bearings are permanently lubricated and sealed to keep out contaminants and reduce maintenance time.
- Towbar-actuated front wheel brakes make it easy to secure the cart to prevent rollaways.
- U.S. military-grade powder coating comes in custom colors with optional hot-dip galvanizing for added protection.

WIDTH	60 inches (152 cm)
LENGTH	120 inches (305 cm)
HEIGHT	48 inches (122 cm)
CAPACITY	8,000 pounds (3,629 kg)
WEIGHT	1,240 pounds (562 kg)
TRACK WIDTH	52-3/4 inches (134 cm)
TIRES	4.00 x 8 solid rubber or 6.90 x 9 pneumatic
KING PIN	2-inch diameter stress-proof with sealed Timken bearings
REAR HITCH	Spring-loaded E-hitch; additional options available
CORNER BUMPERS	Welded steel lower corner bumpers
COVER	Vinyl with webbed reinforcement
RUNNING GEAR	Rigid mount / 4-wheel independent rubber torsion axle

WWW.WASPINC.COM

320.634.5885